

Revised: 9/30/2009

C33

Special Cover coat

1. General Information

C33 is a high stick-able cover coat for silk-screen printing for porcelain, bone china, earthenware and enamel ware.

C33 is especially suitable for relief and four-color printing decal.

2. Technical and Application Data

| | |
|---------------------------------|---|
| Usage | Hand, automatic and semi-automatic screen printing |
| Appearance | Red transparent liquid |
| Substrates | Porcelain, bone china, earthenware, enamel |
| Screens | Polyester 50-70 mesh/21-27T, corresponding steel mesh |
| Composition | Acrylic resin, aromatic naphtha |
| Consistency | Flowing |
| Drying speed | Middle |
| Flash point | 47°C |
| Viscosity (at 25°C) | 1300mPa·s (20rpm) |
| Solids content | 42% |
| Recommended working temperature | 20-30°C |
| Recommended relative humidity | 60-65% |
| Cleaner | TC1 |
| Thinner | TC1, adding less than 10% |
| Blocking stability | Interleaving paper required |
| Hazard classification | Flammable, dangerous goods |

3. Material Safety Data Sheet (MSDS)

Material safety data sheet (MSDS) of C33 is available on request.

The above information and statements are unsolicited. Izawa Pigment Co., Ltd. provides them to promote its products. The above information and statements are also believed to be accurate at the time of publication under their laboratory conditions. Use of them is at the sole discretion of the user and Izawa Pigment Co. Ltd.

does not give any warranty with respect to any test results. In no event shall Izawa Pigment Co., Ltd. be liable for any direct, indirect, special, incidental, or consequential damages arising out of the use of the above information.